## **Steer Axles for Forklift**

Forklift Steer Axles are defined by a central shaft that turns a gear or a wheel. The axle on wheeled motor vehicles could be attached to the wheels and revolved together with them. In this particular situation, bushings or bearings are provided at the mounting points where the axle is supported. Conversely, the axle could be connected to its surroundings and the wheels may in turn revolve all-around the axle. In this situation, a bearing or bushing is located within the hole in the wheel to be able to enable the wheel or gear to revolve around the axle.

When referring to trucks and cars, some references to the word axle co-occur in casual usage. Usually, the term means the shaft itself, a transverse pair of wheels or its housing. The shaft itself turns along with the wheel. It is usually bolted in fixed relation to it and referred to as an 'axle shaft' or an 'axle.' It is equally true that the housing surrounding it which is usually known as a casting is otherwise referred to as an 'axle' or sometimes an 'axle housing.' An even broader sense of the term refers to every transverse pair of wheels, whether they are attached to one another or they are not. Thus, even transverse pairs of wheels within an independent suspension are generally referred to as 'an axle.'

In a wheeled motor vehicle, axles are an essential component. With a live-axle suspension system, the axles work to be able to transmit driving torque to the wheel. The axles likewise maintain the position of the wheels relative to one another and to the motor vehicle body. In this particular system the axles must likewise be able to support the weight of the vehicle plus whichever load. In a non-driving axle, as in the front beam axle in various two-wheel drive light trucks and vans and in heavy-duty trucks, there will be no shaft. The axle in this situation works only as a steering part and as suspension. Many front wheel drive cars have a solid rear beam axle

The axle serves just to transmit driving torque to the wheels in various kinds of suspension systems. The position and angle of the wheel hubs is part of the operating of the suspension system seen in the independent suspensions of new SUVs and on the front of many new light trucks and cars. These systems still have a differential but it does not have attached axle housing tubes. It could be attached to the vehicle body or frame or even can be integral in a transaxle. The axle shafts then transmit driving torque to the wheels. The shafts in an independent suspension system are like a full floating axle system as in they do not support the motor vehicle weight.

To finish, in reference to a vehicle, 'axle,' has a more ambiguous classification. It means parallel wheels on opposing sides of the motor vehicle, regardless of their mechanical connection type to one another and the motor vehicle frame or body.